

## Features:

- AAMA standard Tested and Certified
- 3 1/4" frame depth
- Structural thermal breaks
- Coped corner screw spline design
- Positive meeting rail interlock
- Full width pull handles
- Equal length master frame legs
- Poured and debridged thermal break
- Thermal break debridging is not exposed
- Double fin type weather stripping
- 1" sealed insulating glass per ASTM E 2190-02
- Aluminum glazing beads with dual duroator bulb
- Extruded Aluminum type automatic locks
- Manufactured on 1/8" increments
- Screens in charcoal colored fiberglass mesh.
- XO, XO or XOX Sliding windows
- Kynar 2605 finish in 25 standard colors.

## Options:

- **Lower sightline meeting rail on 953D**
- All commercially available glazing materials
- 1" Glass Pocket for glazing exterior applied grids
- Between-the-glass muntins
- Exterior-applied muntins in 4 different widths
- 1" insulated panels
- Limited sash travel
- Various structural mullions for joining multiple windows in an opening
- Receptor Systems
- Standard and custom panning systems
- Interior trim systems
- Sub-sills
- Project specific custom extrusions
- Aluminum, stainless steel or solar screen mesh
- Custom colors, 2603 Fluorocryl, 2604 Kynar and anodized finishes.

## 9530 and 953D

