

Features:

- AAMA standard tested and certified
- Master frame wall thickness 0.125"
- Vent frame wall thickness 0.125"
- Structural thermal breaks
- Butt construction and triple screwed master frame corner design
- Equal length master frame legs
- Unique 4-raceway thermal break cavity design with 1/4" debridging
- Thermal break debridging is not exposed
- 1" sealed insulating glass per ASTM E 2190-02
- Aluminum glazing beads with Santoprene bulbs
- Manufactured on 1/8" increments
- Kynar 2605 finish in 25 standard colors.

Options:

- Integral mulling of awning (POB), hopper (PIT), casements and fixed in same master frame
- All commercially available glazing materials
- 1 3/8" insulating glass
- 1 3/8" glass pocket for glazing exterior applied grids and maintains 1" insulating glass
- Single glazing
- Between-the-glass muntins
- Exterior-applied muntins in 4 different widths
- 1/4", 1", 1 3/8" 1 1/2" insulated panels
- Split sash designs with dual glazing to accommodate polycarbonate glazing
- Split sash designs to accommodate 5/8" depth between the glass blinds
- Strap anchors to facilitate installation in new construction
- Various structural mullions for joining multiple windows in an opening
- Receptor Systems
- Standard and custom panning systems
- Interior trim systems
- Sub-sills
- Custom colors, 2603 Flurocryn, 2604 Kynar and anodized finishes.