

Features:

- AAMA standard Tested and Certified
- 3 1/4" frame depth
- Side load design
- Structural thermal breaks
- Coped corner screw spline design
- Positive meeting rail interlock
- Full width lift and pull handles
- Equal length master frame legs
- Double fin type weather stripping
- 1" sealed insulating glass per ASTM E 2190-02
- Aluminum glazing beads with dual duroator bulb
- Class 5 reduced lift (Ultra-Lift) balances as required by specifications or sash weight
- Extruded Aluminum type automatic locks
- Manufactured on 1/8" increments
- Vent screens with charcoal colored fiberglass mesh
- Kynar 2605 finish in 25 standard colors.



Options:

- Slide on strap anchors with 1 1/4" extension beyond interior face of the window
- Round tops
- All commercially available glazing materials
- 1" glass pocket for glazing exterior applied grids
- Between-the-glass muntins
- Exterior-applied, in between glass, and tape applied muntins in 4 different widths
- 1" insulated panels
- Limited sash travel
- Various structural mullions for joining multiple windows in an opening
- Receptor Systems
- Standard and custom panning systems
- Interior trim systems
- Sub-sills
- Project specific custom extrusions
- Aluminum, stainless steel or solar screen mesh
- Custom colors, 2603 Fluorocryl, 2604 Kynar, and anodized finishes