

## Features:

- 3 3/4" Frame Depth
- Continuous Frame Design
- Frames Mechanically Fastened
- 3 3/4" Sightline (Inswing)
- 4" Sightline (Outswing)
- Std Equal Length frame legs
- AAMA tested and certified
- Unique 4-raceway thermal break cavity design with 5/16" de-bridging
- Thermal break de-bridging is not exposed
- Adjustable stainless steel 4-bar Anderberg hinges
- Cast white bronze cam-type locking handles
- 5 knuckle hinges with stainless steel
- Friction adjuster/limit device
- Push-pull operation
- 1" sealed insulating glass per ASTM E 2190-02
- Aluminum glazing beads with Santoprene bulb seals
- Inswing/Outswing Operation
- Manufactured on 1/8" increments
- Santoprene bulb weather-stripping

## Options:

- Dual Glazing Insulated & Monolithic for glazing and polycarbonate (or acrylic)
- Hinged Interior Access Panels
- Between-the-Glass Blinds (1", 5/8")
- Unequal or extended leg frames available
- All commercially available glazing materials
- 3 1/4" Glazing pocket to accommodate various glaze combinations.
- Between-the-glass, exterior-applied and true muntins
- Roto-Operators
- Custodial Locks (key-operated)
- Multi-point Locks
- Life Safety opening limiter
- Egress hinges, keyed limited, in hinge flatbar limit stop.
- 3 piece structural mullions
- Subsills, Sill starter, Alcoa Sills
- Receptor, panning and interior trim systems
- Fiberglass (standard), aluminum, stainless steel or solar screen mesh
- Custom colors, 2603 Fluorocryl, 2604 Kynar and anodized finishes

# 1251

## Casement—Outswing

